

VMU

Vetrina a refrigerazione statica per l' esposizione di salumi, latticini e/o prodotti freschi confezionati
Promotional showcase at static refrigeration to display fresh pre-packed food and dairy food



mod. STD



mod. LX

MODELLO / MODEL

100 STD

125 STD


150 STD

MODELLO / MODEL


100 LX

125 LX

150 LX



VMU STD



VMU LX

Caratteristiche tecniche / Technical features

MODELLO	MODEL		100	125	150
Dimensioni esterne (LxPxH)	External dimensions (LxDxH)	mm	1010x725x1150	1260x725x1150	1510x725x1150
Peso netto	Net weight	kg	93	103	116
Capacità (lorda/netta)	Display (gross/net)	litri / litres	217/85	276/107	336/130
Classe climatica di funzionamento	Operating climatic class	N°/°C/RH	3/25/60	3/25/60	3/25/60
Temperatura prodotto	Product temperature	°C	+1/+10	+1/+10	+1/+10
Sbrinamento	Defrosting		F. C. / S. C.	F. C. / S. C.	F. C. / S. C.
Assorbimento elettrico a regime	Electrical input standard	W / A	240/2.3	250/2.4	260/2.4
Assorbimento elettrico a sbrinamento	Electrical input defrosting	W / A	-	-	-

F. C. / S. C.: Fermata Compressore / Stop Compressor