

# HOSHIZAKI

Series



KM1300M\_H 302  
Item # 13034

KM-1300M\_H SERIES



KM-1300MAH  
Air-Cooled  
KM-1300MWH  
Water-Cooled  
KM-1300MRH  
Air-Cooled Remote

KM-1300MAH Cuber  
Shown on Optional  
B-900 Bin

- CycleSaver™ design 
- EverCheck™ alert system 
- Up to 1322 lbs. of ice production per 24 hours
- Individual crescent cube
- Stainless steel evaporator
- Removable air filters



Reliability is a beautiful thing®

© HOSHIZAKI AMERICA, INC.

618 Hwy. 74 S., Peachtree City, GA30269

1-800-438-6087

FAX 1-800-345-1325

TEL 770-487-2331

www.hoshizaki.com


CRESCENT ICE CUBER SLIM-LINE MODULAR

# KM1300M\_H SERIES

# DIMENSIONS (Inches) - CONNECTIONS

## CRESCENT ICE CUBER SLIM-LINE MODULAR

KM-1300MAH (AIR-COOLED)  
 KM-1300MWH (WATER-COOLED)  
 KM-1300MRH (AIR-COOLED REMOTE)



■ Up to 1322 lbs. of ice production per 24 hours



<b>WARRANTY</b> THREEYEAR - Parts & labor on entire machine. FIVEYEAR - Parts & Labor on : Evaporator FIVEYEAR - Parts on: Compressor, Air-Cooled Condenser.	<b>STAINLESS STEEL</b> <b>INTERNAL EVAPORATOR</b>	<b>SERVICE</b> Panels easily removed and all components accessible for service. Removable/cleanable air filters.
	<b>R-404 REFRIGERANT</b>	

Warranty valid in United States, Canada, Puerto Rico, & U.S. Territories. Contact Factory for Warranty in other Countries.

<b>OPTIONAL STORAGE BINS</b> B-500 - 500 lb. Application Capacity (360 lb. ARI-Rated Capacity Bin) B-700 - 700 lb. Application Capacity (550 lb. ARI-Rated Capacity Bin) B-800 - 800 lb. Application Capacity (600 lb. ARI-Rated Capacity Bin) B-900 - 900 lb. Application Capacity (660 lb. ARI-Rated Capacity Bin) B-1200 - 1200 lb. Application Capacity B-1500 - 1500 lb. Application Capacity		<b>ELECTRICAL</b> 208-230/60/1 (3 wire with dedicated neutral for 115V) 20 amp Max Fuse/HACR Breaker Size 1/2" OD copper or equivalent independent potable water supply 3/4" independent drain connection
<b>OPERATING LIMITS</b> Ambient Temp Range 45 - 100°F Water Temp Range 45 - 90°F Voltage Range 187-253V Water Pressure 10 - 113 psig		<b>OPERATING LIMITS:</b> Ambient Temp Range -20°F, +122°F Voltage Range 104 - 127V

### AIR - COOLED

Water Temp° F.	50°	70°	90°
Air Temp° F.	70°	1289	1216
	80°	1233	1120
	90°	1216	1040

### WATER - COOLED

Water Temp° F.	50°	70°	90°
Air Temp° F.	70°	1283	1252
	80°	1259	1211
	90°	1252	1177

### AIR - COOLED REMOTE

Water Temp° F.	50°	70°	90°
Air Temp° F.	70°	1322	1273
	80°	1285	1209
	90°	1273	1155

### UTILITY CONSUMPTION

Model Number	Ice Production Per Cycle		KWH per 100 lbs.	Potable Water Gal. per 100 lbs.	Condenser Water Gal. per 100 lbs.
	Lbs.	Cubes			
KM-1300MAH	28.6	1440	6.2	33.5	NA
KM-1300MWH	28.6	1440	4.5	34.6	113
KM-1300MRH	28.6	1440	5.5	33.6	NA

### SPECIFICATIONS

Model Number	Condenser	Amperage	Min. Circuit Ampacity	Shipping Weight
KM-1300MAH	Air-Cooled	13.2	20	310 lbs.
KM-1300MWH	Water-Cooled	11.5	20	310 lbs.
KM-1300MRH	A-C Remote	13.5	20	310 lbs.

