

HOSHIZAKI

Series



KM1300M_H 302
Item # 13034

KM-1300M_H SERIES



KM-1300MAH
Air-Cooled
KM-1300MWH
Water-Cooled
KM-1300MRH
Air-Cooled Remote

KM-1300MAH Cuber
Shown on Optional
B-900 Bin

- CycleSaver™ design 
- EverCheck™ alert system 
- Up to 1322 lbs. of ice production per 24 hours
- Individual crescent cube
- Stainless steel evaporator
- Removable air filters



Reliability is a beautiful thing®

© HOSHIZAKI AMERICA, INC.

618 Hwy. 74 S., Peachtree City, GA30269

1-800-438-6087

FAX 1-800-345-1325

TEL 770-487-2331

www.hoshizaki.com


CRESCENT ICE CUBER SLIM-LINE MODULAR

KM1300M_H SERIES

DIMENSIONS (Inches) - CONNECTIONS

CRESCENT ICE CUBER SLIM-LINE MODULAR

KM-1300MAH (AIR-COOLED)
 KM-1300MWH (WATER-COOLED)
 KM-1300MRH (AIR-COOLED REMOTE)



■ Up to 1322 lbs. of ice production per 24 hours



WARRANTY THREEYEAR - Parts & labor on entire machine. FIVEYEAR - Parts & Labor on : Evaporator FIVEYEAR - Parts on: Compressor, Air-Cooled Condenser.	STAINLESS STEEL INTERNAL EVAPORATOR	SERVICE Panels easily removed and all components accessible for service. Removable/cleanable air filters.
	R-404 REFRIGERANT	

Warranty valid in United States, Canada, Puerto Rico, & U.S. Territories. Contact Factory for Warranty in other Countries.

OPTIONAL STORAGE BINS

B-500 - 500 lb. Application Capacity (360 lb. ARI-Rated Capacity Bin)
B-700 - 700 lb. Application Capacity (550 lb. ARI-Rated Capacity Bin)
B-800 - 800 lb. Application Capacity (600 lb. ARI-Rated Capacity Bin)
B-900 - 900 lb. Application Capacity (660 lb. ARI-Rated Capacity Bin)
B-1200 - 1200 lb. Application Capacity
B-1500 - 1500 lb. Application Capacity

OPERATING LIMITS

Ambient Temp Range	45 - 100°F
Water Temp Range	45 - 90°F
Voltage Range	187-253V
Water Pressure	10 - 113 psig

ELECTRICAL

208-230/60/1 (3 wire with dedicated neutral for 115V)
20 amp Max Fuse/HACR Breaker Size
1/2" OD copper or equivalent independent potable water supply
3/4" independent drain connection

AIR - COOLED

Water Temp° F.	50°	70°	90°	
Air Temp° F.	70°	1289	1216	1120
	80°	1233	1120	1026
	90°	1216	1040	943

WATER - COOLED

Water Temp° F.	50°	70°	90°	
Air Temp° F.	70°	1283	1252	1182
	80°	1259	1211	1126
	90°	1252	1177	1097

AIR - COOLED REMOTE

Water Temp° F.	50°	70°	90°	
Air Temp° F.	70°	1322	1273	1193
	80°	1285	1209	1121
	90°	1273	1155	1068

UTILITY CONSUMPTION

Model Number	Ice Production Per Cycle		KWH per 100 lbs.	Potable Water Gal. per 100 lbs.	Condenser Water Gal. per 100 lbs.
	Lbs.	Cubes			
KM-1300MAH	28.6	1440	6.2	33.5	NA
KM-1300MWH	28.6	1440	4.5	34.6	113
KM-1300MRH	28.6	1440	5.5	33.6	NA

SPECIFICATIONS

Model Number	Condenser	Amperage	Min. Circuit Ampacity	Shipping Weight
KM-1300MAH	Air-Cooled	13.2	20	310 lbs.
KM-1300MWH	Water-Cooled	11.5	20	310 lbs.
KM-1300MRH	A-C Remote	13.5	20	310 lbs.

